

#### 1D扫描器新选择

1D Area-imaging Scanner is a Good Choice



- 轻松集成
- 内置 RS232 和 USB 接口
- 适应各种场合
- 高速解码和高精度识读能力
- 结实耐用，具有良好的性价比
- Accurate Aimer
- Adapt to a Variety of Occasions
- Build in RS232 and USB Interface
- High Speed, Omni Directional Scanning
- Strong and Durable, With a Good Price

<b>Physical Characteristics</b>	
本体重量Weight ( USB ) :	170g
包装重量Packing Weight ( USB ) :	230g
枪体材质Scanner of Material:	ABS
外观尺寸Dimensions:	112mm X 70mm X 150mm
包装尺寸Packing Size:	220mm X 100mm X 75mm
线材长度Power Line Length:	1500mm
<b>Performance Characteristics</b>	
光源Light Source:	Visible Red Light , Wavelength of 632
光学系统Optical System:	Linear CCD Sensor
处理器Processor:	ARM32-bit
解码速度Decoding Speed:	300 次/秒
解析度Resolution:	≥4mil/0.1mm@PCS90%
提示方式Cue Way:	蜂鸣器Beeper , LED指示灯
接口支持Interfaces Supported:	USB,RS232
电源适配器Power :	Output : DC5V,1A ; Input : AC100~240V; 50~60Hz
电流Current:	30mA (standby); 110mA(Operating)
环境光抗度Ambient Light Immunity:	100,000Lux Max
支持条码类型Barcode:	EAN-8, EAN-13, Codebar, CODE11 , CODE 39, CODE 93, CODE128, China Post, German Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E, UCC/EAN 128, ISBN/ISSN, ISBT , Interleaved 2 of 5 , Matrix 2 of 5 , Industrial 2 of 5 , MSI/Plessey, ITF14.
<b>User Environment</b>	
工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-20°C to 60°C
湿度Humidity:	20% to 95% relative humidity, non-condensing
跌落高度Dropping-height:	1.2M
IP等级:	IP42
Performance may be impacted by bar code quality and environmental conditions	