

## Sunmi M1

## Mobile terminal

Small and portable, single hand free, Read 1D & 2D QR code within 0.7 second. Huge battery, long battery life time. Support 2G/3G, Wi–Fi, Bluetooth. Manage on Sunmi Cloud.









Logistics



Charging base

Project	Main specifications
O/S	Android 5.1
2G/3G	GSM (850/900/1800/1900) + WCDMA (900/2100) GSM (850/900/1800/1900) + WCDMA (850/1900)
CPU frequency	1.3GHz Quad core
LCD screen	4.5" TN, FWVGA 854×480
Touch Screen	Capacity multi-point touch screen
Camera	2.0M FF
Speaker	Mono speaker 1W, Volume up to 90 dB (Adjustable)
Mircrophone	1× MIC, Acoustic wave payment supported
Wi-Fi	Single-band (2.4GHz) single stream. Support 802.11 b/g/n
Bluetooth	Support V2.1+ EDR, 3.0 + HS, V4.0, BLE, iBeacon
Button	Power on button, Volume up/Volume down
Interface	Micro USB debug port, SIM card slot, Audio jack, Charging thimble
Battery	3.7V/3000mAh
Dimension	Terminal: L 148mm × W 73mm × H 23mm Charging Base: L 104mm × W 74mm × H 68mm
Thimble type charging base	Input: AC100~240V/1.5A 50/60Hz Output: DC5V/1A

Note:

Real memory will be reduced due to a number of factors, and there are differences. Operating system also occupy part of memory.
Actual product specifications when sold take precedence over what may be listed at this catalogue; Any changes may be made without prior notification