



XP-370B/370BM

Thermal Barcode Printer

- Compact and space saving design
- Easy paper load with adjustable paper guide
- Printing speed up to 152mm per second
- Max 100mm label diameter, external amount and board option
- Thermal sensitive resistance, photoelectric sensor black mark sensor
- USB+Serial+ethernet or USB+Serial or USB+Bluetooth option

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

XP-370B/370BM

Desktop Barcode Printer



MODEL	XP-370B	XP-370BM
Printing method	Direct thermal	
Resolution	203dpi (8dots/mm)	
Paper width	16~82mm	
Paper roll diameter	25mm (Min) for internal, 100mm (Max) for external	
Printing length (Max.)	1000mm	
Paper thickness	0.06~0.19mm	
Printing speed	Min: 50.8mm/s Max: 152mm/s	
Print head temperature sensor	Thermal sensitive resistance	
Bar Codes	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14 PDF417、QR CODE、Data Matrix	
Print head position sensor	Micro switch	
Media type	Label, Sticker, Continuous, gap, black mark, fan-fold and punched hole	
Paper off type	Tear off & peel off	
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts	
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation	
Gross weight	1.50 kg	
Dimension	231(D) x 163(W) x 150.7(H)mm	
Work enviroment	5~45°C, 20~80%RH	
Storage enviroment	-40~55°C, ≤93%RH(40°C)	
Drivers	Win XP/Win 7/Win 8/Win 10/Android/IOS	
Input	24VDC, 2.5A	
Paper exists detection	Photoelectric sensor	
Interface	USB+Serial	USB+Bluetooth Serial+USB+Lan
Memory	DRAM: 4M; FLASH: 4M	
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.poskeytech.com](http://www.poskeytech.com)
Email: overseas@xprinter.net

