

XP-A200H

Thermal Receipt Printer



Key features

- Desktop or wall-mounted type for option.
- Supports multi 1D barcodes printing.
- Supports black mark detection and order reminding function.
- Supports printing status monitor and anti-losing order function.

Applications



Shopping



Mart



Restaurant



Hospital



Coffee Shop



Ticketing

XP-A200H

Thermal Receipt Printer



MODEL	XP-A200H
Printing method	Direct thermal
Printing speed	200mm/s
Paper width	79.5±0.5mm
Printable area	72mm(adjustable by commands)
Maximum paper diameter	Φ80mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm(Changeable by commands)
Commands	Compatible with ESC/POS
Interface type	USB+Serial / Lan
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Dimension	186×140×146mm (D×W×H)
Gross weight	1.1 kg
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/ CODE128
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)
Cutter	Partial
Cutter life	1.5 million cuts
Print head life	100KM
Input buffer	64 Kbytes
NV Flash	256 Kbytes
Power adaptor	AC110V/220V, 50~60Hz
Power source	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature: 0~45°C, humidity: 10~80RH%
Storage environment	Temperature: -10~60°C, humidity: 10~90RH%
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win 10 /Linux



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
Http://www.poskeytech.com
Email: overseas@xprinter.net

