



XP-S200M/S260M/S300M

Thermal Receipt Printer



- New sleek shell design
- Wall mount capable
- Easy drop-in paper loading
- Intelligent cutter control system
- Order comes remind
- Screen can be added (XP-S300M)



XP-S200M/S260M/S300M

Thermal Receipt Printer



MODEL	XP-S200M/	XP-S260M	XP-S300M
Printing method	Direct thermal		
Printing speed	200mm/s	260mm/s	300mm/s
Paper width	79.5±0.5mm		
Printable area	72mm(adjustable by commands)		
Maximum paper diameter	Φ80 mm		
Paper thickness	0.06-0.08mm		
Column capacity	576 dots/line 512 dots/line		
Line space	3.75mm(Changeable by commands)		
Commands	Compatible with ESC/POS		
Interface type	USB+Serial / USB+Lan		USB+Serial+Lan
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots		
Dimension	180×140×134.1mm(D×W×H)		
Gross weight	0.97 kg		
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128		
2-dimension code	QR CODE / PDF417 (USB+Lan)		
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)		
Cutter	Partial		
Cutter life	1.5 million cuts		
Print head life	100KM		
Input buffer	64 Kbytes	2048 Kbytes	
NV Flash	256 Kbytes		
Power adaptor	AC110V/220V, 50~60Hz		
Power source	DC 24V/2.5A		
Cash drawer output	DC 24V/1A		
Work environment	Temperature: 0~45°C, humidity: 10~80RH%		
Storage environment	Temperature: -10~60°C, humidity: 10~90RH%		
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux		



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
 Http://www.xprintertech.com
 Email: overseas@xprinter.net

