

RETAIL SCALES  
500 RANGE

# WIND series




# 1 LABEL PRINTER (OR RECEIPT)

Pole  
Format



Dimensions



DATA IN mm

- A** 365
- B** 440
- C** 160
- D** 530

Plate (stainless steel):  
L360 x W260 mm



SCALES  
WITH PRINTER

	Displays	Printer	PLUs	Direct PLUs	Vendors	Power	Capacity / Accuracy	Reference
<b>W-015 P</b>	LCD Segment	Labels (or Receipts)	2,000	45x2 + 4x2*	5	Mains	6 kg / 2 g - 15 kg / 5 g	7W151TBLGE__
<b>W-025 P</b>	LCD Segment	Labels (or Receipts)	5,000	40x2 + 9x2*	10	Mains	6 kg / 2 g - 15 kg / 5 g	7W251TBLGE__

\* Using the Shift key and those of Vendor.



**1 PRINTER**  
RECEIPTS  
OR LABELS



**LCD SEGMENT**  
DISPLAY



OPTIONAL  
**LCD GRAPHIC**  
DISPLAY



UP TO  
**5,000 PLUs**



UP TO  
**10 VENDORS**



**ETHERNET**  
TCP/IP



**WI-FI**  
OPTIONAL



OPTIONAL  
RECHARGEABLE  
INTERNAL  
**BATTERY**



**METROLOGICAL**  
VERIFICATION  
OPTIONAL (EU)

## Characteristics and functionality

### Main characteristics

- Electronic scale with higher visibility display options.
- Models with receipt printer or label printer (suitable for receipts).
- Functional and robust design.
- Compliance with EU Regulation 1169/2011 on the provision of food information to consumers (only for W-025).

### Features

- Extensive information for each PLU: normal price, price for weight scales and by kg/100 g (in W-020, W-020 B and W-025), 2 names of 20 characters (1 in W-010, W-010 B and W-015), 10 free texts of 24 characters (5 in W-010, W-010 B and W-015), 1 text of 3,000 characters (in W-025), profitability codes, etc.
- PLU search by code or name.
- Preset keys to programming menus: to change prices, register PLUs or vendors, etc.
- Direct access to 999 PLUs from the keyboard.
- Drill down menu.
- Printing of scale menus.

- 2 programmable macros (in W-020, W-020 B and W-025): recording of a sequence of keys to create direct access to any task (reopening of receipts, lists, change in batcher number, etc.).
- Sales and management reports: sales (by article, vendor, time frames, last month, etc.), balance available in the cash drawer, modified PLUs, etc.
- Fast and reliable communication between scales, with PC and mobile devices (via DWS).
- Stocks management on the scale.
- Option to record normal price for each article.
- Stock / order mode.

### Capacity / Accuracy

- Multirange (3,000 divisions): 6 kg / 2 g - 15 kg / 5 g.
- Optional:
  - > Monorange (3,000 divisions): 15 kg / 5 g or 30 kg / 10 g.
  - > Multirange (3,000 divisions): 15 kg / 5 g - 30 kg / 10 g.
  - > Monorange (6,000 divisions): 12 kg / 2 g or 30 kg / 5 g.

## Available formats

- Flat.
- Pole.

## Construction

- Highly resistant ABS plastic casing.
- Stainless steel plate.

## Displays

- Backlit LCD segment display (W150.2 x H43.4 mm) for vendor and buyer (showing weight, price / kg, total, tare, vendors and name of articles).
- Optional:
  - › LCD matrix graphic display (W134 x H41 mm) for vendor and buyer, for W-020, W-020 B and W-025. Possibility of showing: logos, profitability codes, warning messages sent from a PC (on vendor display) and advertising messages with animated effects on buyer display.

## Printer

- Models available with 1 printer for receipts or 1 printer for labels (also suitable for receipts by changing the paper roll and the working mode).
- 54 mm thermal printer.
- High resolution (8 dots/mm).
- Speed depending on models:
  - › W-020 and W-025: 100 mm/sec.
  - › W-010 and W-015: 80 mm/sec.
  - › W-010 B and W-020 B: 60 mm/sec.

## Receipts

- All the models:
  - › 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
  - › Up to 40 items.
  - › EAN-13 barcode.
  - › 9 payment methods.
  - › Total in National currency and other 3 different currencies.
  - › Discounts per line and total.
- W-010, W-010 B and W-015:
  - › 2 fixed formats.
- W-020, W-020 B and W-025:
  - › 2 fixed formats + 1 programmable format.
  - › 4 logos per receipt.
  - › Name of vendor.
  - › Customers on account.

## Labels

- All the models:
  - › 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
  - › 40 logos.
  - › EAN-13 barcode.
  - › 40 fields of information.
  - › 100 programmable texts.
  - › Manual and automatic pre-packaging modes.
  - › Automatic adjustment of the paper detection option.
- W-015:
  - › From W30 x L30 mm to W60 x L80 mm.
  - › 20 fixed formats + 5 programmable formats.
  - › 1 type of generic traceability (for meat, fish, fruits, vegetables, etc.) up to 10 products. Included in the prevailing European legislation on bovine traceability.
- W-025:
  - › From W30 x L30 mm to W60 x L100 mm.
  - › 20 fixed formats + 10 programmable formats.
  - › 3 levels of totals.
  - › Printing of "n" identical labels.
  - › Printing with 90°, 180° and 270° rotation.
  - › Packaging date, expiry date and extra date (for any application).
  - › Alphanumeric batch number.
  - › 2 types of generic traceability (for meat, fish, fruits, vegetables, etc.) up to 20 products. Included in prevailing European legislation on bovine traceability.



## Food information

- **W-010, W-010 B and W-015:**
  - › Minimum letter size: 1.2 mm.
  - › For direct sale receipts and labels: possibility of indicating in the PLU name (with an \* or other symbol) those that contain allergens and programming a text, such as “\* Consult allergens”.
  - › Labels do not comply with the labelling of packaged food Regulation (only 5 texts of 24 characters are available).
- **W-020 and W-025:**
  - › Minimum letter size: 1.2 mm.
  - › Effect (**bold**, underlined, or **both**) for each character in the text.
  - › Possibility of using the general text “G” (2,048 characters) for ingredients, in lower case or UPPER CASE to highlight allergens.
  - › Possibility of including a table of nutritional facts.
  - › Free texts (10 x 24 characters).
  - › For direct sale receipts and labels: possibility of indicating in the PLU name (with an \* or other symbol) those that contain allergens and programming a text, such as “\* Consult allergens”.
  - › Possibility of printing 2 labels for each operation: programmable by PLU, configurable information, 2<sup>nd</sup> automatic or manual label (also to be used as promotional labels).
- **W-025:** Compliance with EU Regulation 1169/2011 on the provision of food information to consumers as of 13 December 2016.

## Communications

- TCP/IP Ethernet for interconnection and connection to PC.
- RS-232, for connection to scanner (in W-020 and W-025).
- **Optional:**
  - › Wi-Fi.

## Security

- Access to different protected programming menus via configurable passwords.

## Interconnection

- W-010, W-010 B and W-015: up to 5 scales per section.
- W-020, W-020 B and W-025: up to 10 scales per section.

## Connectivity with other devices

- PC.
- Barcode scanner (powered by the scale – 5 VDC) to read EAN-13 barcodes (in W-020, W-020 B and W-025).
- Cash drawer.

## Software (See section on software)

### PC software:

- **DFS:**
  - › Programming of scales.
  - › Receipt of sales data.
  - › Data backup copy.
  - › Graphic design of receipts and labels.
  - › Design and management of advertising images for graphic display.
- **RMS\*:**
  - › Programming and management of scales.
  - \* Does not manage:
    - › Images (of articles and advertising).
    - › Specific functions of Wind scales.
- **DLD:**
  - › Graphic design of receipts and labels.
- **Integration tools: in Windows or Linux to facilitate communication with the Back-Office.**

### Scale firmware:

- **DWS (Dibal Web Server):**
  - › Allows access to the information on each scale from any computer or mobile device with an Internet browser.

## Power supply

- Mains: 110 up to 230 VDC.
- Depending on the models, also:
  - › High performance rechargeable internal battery (W-010 B and W-020 B): up to 36 hours of life (calculated for 1,000 receipts, with 3 articles per receipt)\*\* and connector to external battery 12 V.
  - › Anti-blackout rechargeable internal battery 24 V and connector to external battery 24 V.

\*\* With segment display and back lighting disconnected. The charging and autonomy times may vary considerably in accordance with the temperature, age and condition of the batteries, use of back lighting, frequency of use of the printer, interconnection, etc.